

Premium Collection

HIGH-QUALITY VINYL FLOORING FOR A WIDE RANGE OF USES, FROM EDUCATION AND HEALTHCARE TO OFFICES AND PUBLIC BUILDINGS

Easy to clean and maintain

Enhanced life cycle cost

2mm wear layer for extreme durability and co-ordinating welding rods for a perfect finish


Phthalate free, 100% recyclable and Restart ready

Combine
& Create

Primo Premium



2101 0672 LIGHT WARM GREY
[MULTICOLOUR WELD ROD: 1290220]
LRV 56




2101 0665 MEDIUM BLUE
[MULTICOLOUR WELD ROD: 1290164]
LRV 27



2101 0678 LIGHT BEIGE
[MULTICOLOUR WELD ROD: 1290232]
LRV 71



2101 0659 DARK WARM BEIGE
[MULTICOLOUR WELD ROD: 1290160]
LRV 39



2101 0680 MEDIUM GREEN
[MULTICOLOUR WELD ROD: 1290059]
LRV 37



2101 0670 MEDIUM PURE GREY
[MULTICOLOUR WELD ROD: 1290222]
LRV 56




2101 0675 LIGHT COOL BEIGE
[MULTICOLOUR WELD ROD: 1290229]
LRV 62


Eclipse Premium



2102 0040 ECLIPSE CLASSIC MEDIUM GREY
[MULTICOLOUR WELD ROD: 1290189]
LRV 34



2102 0717 ECLIPSE SPIRIT MEDIUM GREY
[MULTICOLOUR WELD ROD: 1290170]
LRV 30



2102 0972 ECLIPSE SPIRIT LIGHT BEIGE
[MULTICOLOUR WELD ROD: 1290128]
LRV 71

NATIONAL FLOORING

 Tarkett

Premium Collection

TECHNICAL DATA

CLASSIFICATION	STANDARD	PRIMO PREMIUM	ECLIPSE PREMIUM
Type of floor covering	ISO 10581	Homogeneous vinyl flooring	Homogeneous vinyl flooring
Classification	EN ISO 10874	Commercial 34 Industrial 43	Commercial 34 Industrial 43
Wear layer binder content	ISO 10581	Type I	Type I
TECHNICAL CHARACTERISTICS	STANDARD	PRIMO PREMIUM	ECLIPSE PREMIUM
Total thickness	EN ISO 24346	2.00mm	2.00mm
Total weight	EN ISO 23997	3000g/m ²	3000g/m ²
Form of delivery	EN ISO 24341 Sheet (rolls) EN ISO 24342 Tiles (box)	Approx. 23 lm x 200 cm Art. no. 21010 ___ 3 digit colour number 61 x 61 cm - 14 tiles/box = 5.21 m ² Art. no. 21011 ___ 3 digit colour number	Approx. 23 lm x 200 cm Classic / Spirit: Art. no. 21020 ___ 3 digit colour number 61 x 61 cm - 16 tiles/box = 5.95 m ² Classic / Spirit: Art. no. 21021 ___ 3 digit colour number 30 x 30 cm - 50 tiles/box = 4.50 m ² Classic / Spirit: Art. no. 21022 ___ 3 digit colour number
TECHNICAL PERFORMANCES	STANDARD	PRIMO PREMIUM	ECLIPSE PREMIUM
Surface treatment		PUR reinforced	PUR reinforced
Residual indentation	ISO 24343-1 (EN 433)	Required value: ≤0.10mm Best measured value*: 0.03 mm	Required value: ≤0.10mm Best measured value*: 0.03 mm
Castor chair	ISO 4918 (EN 425)	No damage	No damage
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1 ≥8kW/m ² Pass	Class Bfl-s1 ≥8kW/m ² Pass
Electrostatic properties	EN 1815 EN 1081 EN 14041	≤2kV on concrete <10 ⁹ Ω on concrete Antistatic on concrete	≤2kV on concrete <10 ⁹ Ω on concrete Antistatic on concrete
Thermal resistance	EN 12667 / DIN 52612	0.01m ² K/W	0.01m ² K/W
Slip resistance	EN 13893 BS 7976-2 DIN 51130	≥0.3 Low risk of slip R9	≥0.3 Low risk of slip R9
Clean room test	ASTM F24 F51 ISO 14644-1	Class A ISO class 4	Class A
Ease of decontamination	ISO 8690	Good	Good
Chemical resistance	ISO 26987	Good resistance	Good resistance
Bacteria resistance	EN ISO 846: Part C	Does not favour growth	Does not favour growth
Flexibility	ISO 24344	Pass	Pass
Dimensional stability	ISO 23999 (EN 434)	≤ 0.40 % for rolls / ≤ 0.25 % for tiles	≤ 0.40 % for rolls / ≤ 0.25 % for tiles
Seam strength	EN 684	Individual values: ≥ 400N/50 mm	Individual values: ≥ 400N/50 mm
Light fastness	EN ISO 105-B02	≥6	≥6
Underfloor heating		Suitable - Max 27°C	Suitable - Max 27°C
Total VOC emissions	ISO 16000-9 Indoor air quality	≤ 10µg/m ³ (after 28 days) Platinum	≤ 10µg/m ³ (after 28 days) Platinum
Colours		7	3
CE MARKING	STANDARD	PRIMO PREMIUM	ECLIPSE PREMIUM
DoP number	EN 14041	0019-0018-DoP-2013-07	0019-0020-DoP-2013-07

*For information - not binding.

Please note colours, grains and textures may vary when compared to the full size product or when viewing this sample card in digital format. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett for these instructions or to request a sample to ensure accuracy.

All information was correct at the time of publication (06/2021) but is subject to modification for the benefit of further improvement to the product.



Tarkett's commitments to VOC* emissions

Volatile Organic Compounds (VOCs) are emitted as gases from man made materials such as flooring as well as natural ones like trees. To improve indoor air quality Tarkett has invested significantly in the research of raw materials and the flooring manufacturing process to reach a near zero emission level. Since September 2011 all commercial floors that Tarkett manufacture release emissions below quantifiable levels - measuring less than 10 µg/m³ TVOC after 28 days - hundred times lower than European standards. Continued focus on safer, healthier and sustainable solutions that reduce emissions for improved indoor air quality and a healthier quality of life is a focus across all our product portfolio.

*ISO Standards 16000-3/-6/-9/-11

07/2021 V1

TARKETT LIMITED

LENHAM OFFICE
Dickley Lane
Lenham
Maidstone
Kent
ME17 2QX
United Kingdom

ASHFORD OFFICE
4th Floor
1 Dover Place
Ashford
Kent
TN23 1FB
United Kingdom

Tel 0800 3282115
Email: uksales@tarkett.com
Website: tarkett.co.uk
Twitter: [@tarkettUK](https://twitter.com/tarkettUK)

