


Linoleum sheet floorcovering


- ▣ Sustainable and made with natural and renewable ingredients
- ▣ Unique homogeneous construction
- ▣ Superior xf² surface protection for extreme toughness
- ▣ Easy cleaning and maintenance - no polish, no stripping or waxing over lifetime of product
- ▣ 20 timeless colours guaranteed until 2033 with multicolour welding rods for a perfect finish

LINOLEUM


Veneto
xf²




Pebble 14872 604 LRV 63.53



Smoke 14872 608 LRV 51.64



Charcoal 14872 610 LRV 29.99



Sisal 14872 611 LRV 79.29



Corn 14872 612 LRV 85.58



Camel 14872 616 LRV 78.87




Amber 14872 636 LRV 70.58



Terracotta 14872 641 LRV 50.87



Grass 14872 650 LRV 58.38



Horizon 14872 663 LRV 71.84




Zinc 14872 671 LRV 68.10



Aluminium 14872 672 LRV 64.83



Steel 14872 673 LRV 53.30



Slate 14872 674 LRV 28.67



Cork 14872 679 LRV 84.00



Storm 14872 702 LRV 72.56




Neutral 14872 710 LRV 80.14



Ecrú 14872 711 LRV 83.22



Grey 14872 793 LRV 81.73



Graphite 14872 906 LRV 40.80


LINOLEUM

Veneto xf²


Specification

Linoleum homogeneous floorcovering on jute backing. Composition - Linseed oil, wood and cork flour, natural resins, pigments.

Product Standard EN ISO 24011 (EN 548)



Linoleum floors to EN 548 have a generic A+ environmental rating in major use areas such as healthcare and education. www.bre.co.uk/greenguide



According to European Classification EN ISO 10874 (EN 685)



Certification	Standards	Veneto Linoleum xf ²
Type of floorcovering	EN ISO 24011 (EN 548)	
Classification	EN ISO 10874 (EN 685)	Domestic 23 Commercial 34 Light Industrial 43
Technical Performances	Standards	Veneto Linoleum xf ²
Surface treatment		xf ²
Total thickness	EN ISO 24346 (EN 428)	2.5 mm
Total weight	EN ISO 23997 (EN 430)	3000g/m ²
Form of delivery	EN ISO 24341 (EN 426)	Rolls: 30 lm x 2m 14872 _ _ _ (3 digit colour no.)
Technical Performances	Standards	Veneto Linoleum xf ²
Residual indentation	EN ISO 24343-1 (EN 433)	ca. 0.08 mm
Castor chair	ISO 4918 (EN 425)	Suitable for office chairs with castors type W (norm EN 12529)
Flexibility	EN ISO 24344 (EN 435) (Method A)	≤ 30mm Ø
Reaction to fire	EN 13501-1	Cfl s1
Static electrical propensity	EN 1815	< 2 kV
Impact sound reduction	ISO 140-8 EN ISO 717/2	≤ 6 dB
Light fastness	EN ISO 105-B02 Method 3	≥ 6
Chemical resistance	EN ISO 26987 (EN 423)	Resistant to dilute acids, oils, fats and current solvents and alkalis
Thermal resistance	ISO 10456 (EN 12524)	0.015 m ² K/W
Underfloor heating		Suitable
Determination of antibacterial activity	ISO 22196	Yes, naturally
Slip Resistance	DIN 51130	R9
Colours		20*

*72 colours available in the complete Veneto xf² range. The above information is subject to modifications for the benefit of further improvement. (06/2014). Tarkett's instructions regarding installation and maintenance should be observed. Please contact Tarkett at the address shown for these instructions. To obtain the exact colour of the samples in this card, it is recommended to expose them to sunlight for several hours in order to remove the normal yellowing effect due to the oxydation process.

Colour name	Reference	Multicolour Welding rod	Unicolour Welding rod
Pebble	14872 604	14000604	1751604
Smoke	14872 608	14000608	1751608
Charcoal	14872 610	14000610	1751610
Sisal	14872 611	14000611	1751611
Corn	14872 612	14000612	1751612
Camel	14872 616	14000616	1751616
Amber	14872 636	14000636	1751636
Terracotta	14872 641	14000641	1751641
Grass	14872 650	14000650	1751650
Horizon	14872 663	14000663	1751663
Zinc	14872 671	14000671	1751671
Aluminium	14872 672	14000672	1751672
Steel	14872 673	14000673	1751673
Slate	14872 674	14000674	1751674
Cork	14872 679	14000679	1751679
Storm	14872 702	14000702	1751702
Neutral	14872 710	14000710	1751637
Ecru	14872 711	14000711	1751679
Grey	14872 793	14000793	1751793
Graphite	14872 906	14000906	1751686

Tarkett Limited Lenham, Maidstone, Kent ME17 2QX, United Kingdom. Tel 01622 854040 Fax 01622 854520 www.tarkett.co.uk Email: uksales@tarkett.com



THE ULTIMATE
FLOORING EXPERIENCE