



# CENTRA

Strong solutions



**HETEROGENEOUS VINYL**

---


# Centra

A function for every layer


Five layers, each with their own specific function, combined into one strong unit. The result: a robust bind between all layers. Moreover, every Tirreno 70 floor has an additional Hyperguard+® PUR protective layer, safeguarding the floor from scratches and dirt. The glass fibre layer, finally, makes for ultimate dimensional stability: the floor will not show any signs of piercing or swelling, even under intensive use.




## Benefits




Strong multi-purpose flooring



Low maintenance



Natural good looks



Installation comfort



Sedna T92



Sedna T06

Centra

## The Collection

---

**06-07**  
SEDNA

**08-09**  
LONDON STONE  
ARTEX

**10-11**  
BOTTICELLI  
ASPIN  
ALLURE

---










BEYOND  
FLOORING



Sedna T14

BEYOND  
FLOORING

## Centra Sedna

 <p>↑↓ Sedna T06 - 2/4 m PR: 100 x 100 cm</p>	 <p>↑↓ Sedna T32 - 2/3/4 m PR: 100 x 100 cm</p>	 <p>↑↓ Sedna T44 - 2/4 m PR: 100 x 100 cm</p>
<p>LRV 61 WR 402</p>	<p>LRV 49 WR 455</p>	<p>LRV 25 WR 431</p>
 <p>↑↓ Sedna T36 - 2/3/4 m PR: 100 x 100 cm</p>	 <p>↑↓ Sedna T14 - 2/4 m PR: 100 x 100 cm</p>	 <p>↑↓ Sedna T99 - 2/4 m PR: 100 x 100 cm</p>
<p>LRV 45 WR 455</p>	<p>LRV 32 WR 464</p>	<p>LRV 13 WR 496</p>
 <p>↑↓ Sedna T92 - 2/4 m PR: 100 x 100 cm</p>	 <p>↑↓ Sedna T94 - 2/3/4 m PR: 100 x 100 cm</p>	 <p>↑↓ Sedna T75 - 2/3/4 m PR: 100 x 100 cm</p>
<p>LRV 48 WR 409</p>	<p>LRV 23 WR 408</p>	<p>LRV 17 WR 479</p>


LRV - Light Reflectance Value / WR - Matching Welding Rod / PR - Pattern Repeat




Artex T30

BEYOND  
FLOORING


Centra  
**London Stone - Artex**



London Stone T93 - 2/4 m LRV 38  
PR: 200 x 150 cm WR 416



London Stone T96 - 2/4 m LRV 10  
PR: 200 x 150 cm WR 496



Artex T95 - 2/4 m LRV 28  
PR: 100 x 100 cm WR 431



Artex T92 - 2/4 m LRV 46  
PR: 100 x 100 cm WR 407



Artex T30 - 2/4 m LRV 51  
PR: 100 x 100 cm WR 432

LRV - Light Reflectance Value / WR - Matching Welding Rod / PR - Pattern Repeat



Centra  
**Botticelli - Aspin - Allure**



↑↑  
**Botticelli T93** - 2/4 m LRV 40  
 PS: 12,5 x 60 cm WR 409  
 PR: 100 x 120 cm



↑↑  
**Botticelli T96** - 2/4 m LRV 15  
 PS: 12,5 x 60 cm WR 449  
 PR: 100 x 120 cm



↑↑  
**Aspin T49** - 2/4 m LRV 21  
 PS: 14,37 x 100 cm WR 446  
 PR: 100 x 100 cm



↑↑  
**Allure T18** - 2/4 m LRV 15  
 PS: 16,6 x 120 cm WR 446  
 PR: 99,5 x 120 cm



↑↑  
**Allure T45** - 2/4 m LRV 25  
 PS: 16,6 x 120 cm WR 430  
 PR: 99,5 x 120 cm

Botticelli T93

BEYOND  
 FLOORING

LRV - Light Reflectance Value / WR - Matching Welding Rod / PS - Plank Size / PR - Pattern Repeat



Camargue T51

BEYOND  
FLOORING

Centra  
**Camargue - Calais**  
**Sorbonne - Chaparral Oak**



**Calais T30** - 2/4 m  
PS: 20 x 120 cm  
PR: 100 x 120 cm

LRV 44  
WR 433



**Camargue T10** - 2/4 m  
PS: 10 x 50/70-60/60 cm  
PR: 100 x 120 cm

LRV 40  
WR 455



**Camargue T51** - 2/3/4 m  
PS: 10 x 50/70-60/60 cm  
PR: 100 x 120 cm

LRV 47  
WR 436



**Camargue T52** - 2/3/4 m  
PS: 10 x 50/70-60/60 cm  
PR: 100 x 120 cm

LRV 30  
WR 435




**Camargue T93** - 2/4 m  
PS: 10 x 50/70-60/60 cm  
PR: 100 x 120 cm

LRV 30  
WR 443



**Sorbonne T97** - 2/4 m  
PS: 16,7 x 100 cm  
PR: 99,5 x 100 cm

LRV 19  
WR 492



**Chaparral Oak T98** - 2/4 m  
PS: 16,5 x 100 cm  
PR: 99,5 x 100 cm

LRV 22  
WR 492

LRV - Light Reflectance Value / WR - Matching Welding Rod / PS - Plank Size / PR - Pattern Repeat

PLEASURE IN THE JOB

# Centra

## Technical Specifications

Spécifications techniques - Technische specificaties - Technische Spezifikationen

<b>Flooring type</b> / Type de couverture - Type vloer - Fußbodenart		Compact Flooring
<b>Heterogeneous PVC</b> / PVC hétérogène - Heterogene PVC - Heterogene PVC	EN ISO 26986	
<b>Level of use</b> / Classe d'usage - Gebruiksklasse - Eignungsklasse	EN ISO 10874	23 - 34 - 43
<b>Total thickness</b> / Epaisseur totale - Totale dikte - Gesamtdicke	EN ISO 24346	2,00 mm
<b>Wear layer</b> / Couche d'usure - Slijtlaag - Nutzschiicht	EN ISO 24340	0,70 mm
<b>Wear layer PUR treatment</b> / Traitement polyuréthane - PUR slijtlaag behandeling - Schutz vor Schmutz PUR		HyperGuard+
<b>Total weight/m<sup>2</sup></b> / Poids total/m <sup>2</sup> - Totaal gewicht/m <sup>2</sup> - Gewicht/m <sup>2</sup>	EN ISO 23997	ca. 2.543 g
<b>Width</b> / Largeur - Breedte - Breite	EN ISO 24341	2-4 m
<b>Standard Length</b> / Longueur standard - Standaardlengte - Standardlänge	EN ISO 24341	ca. 25 m
<b>Weight of standard roll</b> / Poids standard des rouleaux - Standaard rolgewicht - Standard-Rollengewicht		ca. 131 - 262 kg
<b>Inflammability</b> / Classement feu - Brandklasse - Brandverhalten	EN 13501	Bfl-S1
<b>Slip resistance</b> / Glissance - Antislip - Rutschfest	EN 13893	DS
<b>Slip restraint</b> / Résistance au glissement - Slipweerstand - Rutschhemmung	DIN 51130	R10
<b>Residual indentation</b> / Poinçonnement rémanent - Restindruk - Eindrückverhalten	EN ISO 24343-1	0,05 mm (norm ≤ 0,20 mm)
<b>Furniture leg resistance</b> / Résistance au pied de meuble - Meubelpoottest - Möbelschubtest	EN ISO 16581	Very good
<b>Curling</b> / Incurvation - Krulling - Schüsselung	EN ISO 23999	≤ 8 mm
<b>Electrical resistance</b> / Résistance électrique - Elektrische weerstand - Elektrischer Widerstand	EN ISO 10965	10° Ohm
<b>Static electrical propensity</b> / Accumulation de charges électrostatiques - Electrostatistische Propensiteit - Elektrostatische Verhaltung	EN 1815	≤ 2kV (antistatic)
<b>Dimensional stability</b> / Stabilité dimensionnelle - Dimensionele stabiliteit - Massänderung	EN ISO 23999	0,05% (norm ≤ 0,40%)
<b>Thermal conductivity</b> / Conductivité thermique - Warmtedoorgangcoëfficiënt - Wärmeleitfähigkeit	EN ISO 10456	0,25 W/(m.K)
<b>Heat insulation</b> / Isolation thermique - Thermische isolatie - Wärmedurchlasswiderstand	EN ISO 12664	0,0080 (m <sup>2</sup> .K/W)
<b>Binder quantity in wear layer</b> / Taux de liant dans la couche d'usure - Hoeveelheid bindmiddel in slijtlaag - Bindemittelmengde in der Nutzschiicht	EN ISO 10582	Type I
<b>Abrasion group</b> / Groupe d'abrasion - Slijtageweerstand - Verschleißverhalten	EN 660-2	Class T
<b>Indoor air quality</b> / Qualité de l'air intérieur - Binnenmilieu - Raumluftqualität		LOW VOC
<b>Acoustic insulation</b> / Efficacité acoustique - Kontaktgeluidisolatie - Trittschallverbesserungsmaß	EN ISO 717-2	ΔLw 7 dB
<b>Castor chair resistance</b> / Résistance aux chaises à roulettes - Bestand tegen stoelwielen - Stuhlrollenfestigkeit	EN ISO 4918	Pass
<b>Castor type</b> / Type de chaises à roulettes - Type stoelwielen - Stuhlrolle Typ	EN 12529	Type W
<b>Light fastness</b> / Résistance à la lumière - Lichtechtheid - Lichtechtheit	ISO 105B02	6
<b>Underfloor heating</b> / Chauffage par le sol - Vloerverwarming - Bodenheizung	EN 12524	Suitable
<b>Resistance to chemicals</b> / Résistance aux produits chimiques - Chemicalienresistentie - Chemikalienbeständigkeit	EN ISO 26987	Very good
<b>Hot welding</b> / Soudage thermique - Warm lassen - Thermische Verschweißung		Available
<b>Cold welding</b> / Soudage à froid - Koud lassen - Kaltverschweißung	Invisiweld	Suitable
<b>Warranty years</b> / Garantie ans - Garantie in jaren - Garantie Jahren		5

The warranty covers manufacturing defects and premature wear in the event of normal use | La garantie couvre les vices de fabrication et l'usure précoce en usage normal  
De garantie dekt fabricagefouten en voortijdig afslijten bij normaal gebruik | Die Garantie deckt Herstellungsfehler und vorzeitigen Verschleiß bei normaler Nutzung

IVC reserves the right to change or amend any written information without notice.  
Ensure the latest information is being consulted by referring to the website.



NATIONAL FLOORING

Artex T 95



## Get in touch

Want to learn more about National Floorings range of flooring solutions or need help planning a new project? We've got you covered.

You can also make an appointment with our expert team.

Phone us: +353 21 4374484

Email: [info@nationalflooring.ie](mailto:info@nationalflooring.ie)

Go to [www.nationalflooring.ie](http://www.nationalflooring.ie) to browse our collections.



Artex T92